

**Model Information****Main Features**

- Universal PCI 3.3 / 5.0V
- 4x RS232
- 16C950 (128 Byte FIFO)
- 921 kbps
- PCI Plug and Play
- IRQ Interrupt sharing, only one Interrupt per card
- Drivers for Windows 95 to 7/2008 R2
- Software compatible with DOS, Windows 3.11, OS/2, Linux and div. Unix

[Contact Online...](#)

## VScom 400H v3 UPCI

Quick Link: | [Main Features](#) | [More Pictures](#) | [Overview](#) | [Hardware Specifications](#) | [High Performance Features](#) | [Operating Systems](#) | [Ordering Information](#) |

**More Pictures**

Click on the thumbnails for the large picture ...

[> Back to top](#)

**Overview**

The high speed serial ports with their 128 byte long FIFO are best for high speed communication, even in heavy loaded systems. Many unique features reduce the system load. They also allow very unusual speed settings such as 500.000bps.

**Hardware Specifications**

<b>Ports</b>	4x RS232 (Rx, Tx, RTS, CTS, DTR, DSR, DCD, RI)
<b>UART</b>	4x 16C950 (128 Byte FIFO)
<b>Address</b>	Plug and Play
<b>Interrupts</b>	PCI Plug and Play, only one interrupt/card
<b>Speed</b>	max. 921 kbps
<b>Bus interface</b>	Universal PCI. 3.3V / 5.0V
<b>Connectors</b>	2x DB9; 2 x DB9 male (2. Slot)
<b>Temperature</b>	0°C - 55°C

[> Back to top](#)

**High Performance Features**

<b>FIFO</b>	adjustable FIFO length, 1 up to 128Bytes separate adjustable Rx and Tx
<b>Handshake</b>	RTS / CTS DTR / DSR Xon / Xoff all handshake automatic on Chip


<b>Speed</b>	1bps up to 921kbps unusual Baudrates Multiplication factor for legacy applications
<b>Access</b>	high speed access via Memory
<b>UART</b>	UART emulation of 8250 up to 16850
<a href="#">&gt;Back to top</a>	
<b>■ Operating Systems</b>	
<b>Windows 2000 up to 7</b>	VScom high performance serial driver, x86 and x64 Editions
<b>Server 2000 to 2008 R2</b>	VScom high performance serial driver, x86 and x64 Editions
<b>Windows NT 4.0</b>	VScom high performance serial driver control panel applet
<b>Windows 95, 98, SE, ME</b>	VScom high performance serial driver
<b>DOS</b>	virtuellt address driver and compatibility tools real DOS Com port emulation
<b>OS/2</b>	Supported by COM16 driver in recent system releases Third party serial driver SIO.SYS available
<b>Linux</b>	Kernel 2.6 and up: built-in support Previous kernel: VScom high performance real tty driver
<b>div.UNIX</b>	configuration instructions

<a href="#">&gt;Back to top</a>	
<b>■ Ordering Information</b>	
<b>Part Number</b>	4429
<b>Product Name</b>	VScom 400H UPCI
<b>Packing list</b>	VScom 400H UPCI card 2nd Bracket with 2 Ports RS232 DSUB 9 male CD, English documentation

- \* Specifications are subject to change without notice.
- \* All trademarks and brands are property of their rightful owners.

## VScom 400H v3 uPCI

[>Back](#)



(2017 Jul 27)