

Model Information



■ Main Features

- 4x RS232
- 4x 16C550 UARTs (16 Byte FIFO, max. 921 kbps)
- possible I/O-addresses 0h..FFFh
- no jumper, configured by software
- Software compatibel with DOS, Win3.x/95/98/ME/NT 4.0, Win2000, Linux, OS/2, Netware

[Contact Online...](#)

C104H

Quick Link: | [Main Features](#) | [Hardware Specifications](#) | [Ordering Information](#) |

■ Hardware Specifications

Ports	4 x RS232
UART	4x 16C550 (16 Byte FIFO)
Address	0h .. FFF8h
Interrupts	IRQ2 .. IRQ15, supports Interruptsharing
Speed	max. 921 kbps
Bus interface	ISA
Connectors	1x DB37 female
Size	L15.7cm x H8.3cm
Temperature	0°C - 55°C
Operating Systems supported	compatible to DOS, Win3.x/95/98/ME/NT/2000, OS/2, Unix, Linux and Netware
Driver	DOS, Win3.x/95/NT, Linux

[>Back to top](#)

■ Ordering Information

Article No.	745
Product Name	C104H
Packing List	Moxa C104H Pro, cable (DB37 to 4 x DB25 male, cablelength 30 cm), disk (DOS, Windows), German documentation

[>Back to top](#)

* Specifications are subject to change without notice.

* All trademarks and brands are property of their rightful owners.

