

Model Information**Main Features**

- 4x RS422 / RS485
- 32-bit universal PCI
- Supports 64 Byte FIFO Driver
- Embedded 16KV ESD protection
- Support Automatic Data Direction Control (ADDC)
- Built-in termination resistors
- Compact board size (half-size), suitable for any PC c

[Contact Online...](#)

CP-134U PCI

Quick Link: | [Main Features](#) | [More Pictures](#) | [Overview](#) | [Specification](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Configuration](#) | [Power and Environment](#) | [Ordering Information](#) |

More Pictures

Click on the thumbnails for the large picture ...

[>Back to top](#)

Overview

The CP-134 Universal PCI series is designed the new slot standard for expansion Boards and works with both 3.3V and 5.0V server slots. CP 132U offers two independent RS422 / 485, and each port can control up to 32 devices in a multidrop environment.

Specification**Hardware**

I/O controller 4x 16C550C or compatible

Connector type Male DB9

[>Back to top](#)

Interface

Bus interface 32-bit Universal PCI, for 3.3V and 5.0V expansion Slots

Serial interface RS422 / 485

No. of ports 4

Signals RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND
RS485 Data+/-, GND

RS485 data control Auto (Automatic Data Direction Control) or by RTS

Built-in termination resistor RS422 120 Ohm
RS485 120 Ohm, jumper enable / disable

[>Back to top](#)

Performance

Speed 50 - 921.6 Kbps

Max. no. of ports 16 (4 boards)

[>Back to top](#)

■ Configuration

Parity	None, even, odd, space, mark
Data bits	5, 6, 7, 8
Stop bits	1, 1.5, 2
IRQ	Assigned by BIOS
I/O address	Assigned by BIOS

[>Back to top](#)

■ Power and Environment

Power requirement	310mA max.(+5V)
Operation temp.	0°C - 55°C
Dimension	135mm x 110mm
Isolation Protection	16KV ESD protection
Operating Systems supported	Vista, XP, Windows 2000, Windows NT, Windows 95/98/ME, Linux

[>Back to top](#)

■ Ordering Information


Part Number	749
Product Name	CP-134U PCI
Packing list	CP-134U PCI Software CD, English documentation 4 Port DB9 male connection cable Standard Bracket

[>Back to top](#)

- * Specifications are subject to change without notice.
- * All trademarks and brands are property of their rightful owners.

CP-134U PCI

[>Back](#)



(2017 Jul 27)